



Declaration of Performance

FM-X5

Multi-expansion long plug for Concrete and Masonry



1. Identification of the product: **FM-X5**

2. Identification code (art. 11.4), for the batch or serial number see packaging:

FM-X5 countersunk head + screw with countersunk head

d _{nom} ⁴⁾	L ⁵⁾ [mm]	t _{fix} ⁶⁾ [mm]	Marking	Cod. with screw zinc galvanised 5µm	Cod. with screw grey galvanised 10µm	Cod. with screw Stainless steel A4-70
Ø8	80	10	FM-X5 Ø8x80 - 10	64301b08080	64301c08080	64301008080
	100	30	FM-X5 Ø8x80 - 30	64301b08100	64301c08100	64301008100
	120	50	FM-X5 Ø8x80 - 50	64301b08120	64301c08120	64301008120
	150	70	FM-X5 Ø8x80 - 70	64301b08150	64301c08150	64301008150
	170	100	FM-X5 Ø8x80 - 100	64301b08170	64301c08170	64301008170
Ø10	85	15	FM-X5 Ø10x85 - 15	64301b10085	64301c10085	64301010085
	100	30	FM-X5 Ø10x100 - 30	64301b10100	64301c10100	64301010100
	115	45	FM-X5 Ø10x115 - 45	64301b10115	64301c10115	64301010115
	135	55	FM-X5 Ø10x135 - 55	64301b10135	64301c10135	64301010135
	160	90	FM-X5 Ø10x160 - 90	64301b10160	64301c10160	64301010160
	200	130	FM-X5 Ø10x200 - 130	64301b10200	64301c10200	64301010200
	230	160	FM-X5 Ø10x230 - 160	64301b10230	64301c10230	64301010230

FM-X5 countersunk head + screw with hexagonal head

d _{nom} ⁴⁾	L ⁵⁾ [mm]	t _{fix} ⁶⁾ [mm]	Marking	Cod. with screw zinc galvanised 5µm	Cod. with screw grey galvanised 10µm	Cod. with screw Stainless steel A4-70
Ø10	85	15	FM-X5 Ø10x85 - 15	64302b10085	64302c10085	64302010085
	100	30	FM-X5 Ø10x100 - 30	64302b10100	64302c10100	64302010100
	115	45	FM-X5 Ø10x115 - 45	64302b10115	64302c10115	64302010115
	135	55	FM-X5 Ø10x135 - 55	64302b10135	64302c10135	64302010135
	160	90	FM-X5 Ø10x160 - 90	64302b10160	64302c10160	64302010160

FM-X5 with collar head + screw with hexagonal head

d _{nom} ⁴⁾	L ⁵⁾ [mm]	t _{fix} ⁶⁾ [mm]	Marking	Cod. with screw zinc galvanised 5µm	Cod. with screw grey galvanised 10µm	Cod. with screw Stainless steel A4-70
Ø10	85	15	FM-X5 Ø10x85 - 15	64402b10085	64402c10085	64402010085
	100	30	FM-X5 Ø10x100 - 30	64402b10100	64402c10100	64402010100
	115	45	FM-X5 Ø10x115 - 45	64402b10115	64402c10115	64402010115
	135	55	FM-X5 Ø10x135 - 55	64402b10135	64402c10135	64402010135
	160	90	FM-X5 Ø10x160 - 90	64402b10160	64402c10160	64402010160

⁴⁾ Diameter of anchor sleeve; ⁵⁾ Length of anchor; ⁶⁾ Thickness fixture max.

3. Intended use:

Generic type	Plastic anchor for multiple use in concrete and masonry
Base material (use category)	> A: Normal Weight Concrete acc. to EN 206-1 > B: Solid Masonry acc. to EN 771-1 > C: Hollow or Perforated Masonry acc. to EN 771-1 and EN 771-3 > D: Autoclaved Aerated Concrete acc. to EN 771-4
Material of plug	> Sleeve: Polyamide Pa6 acc. to ISO 1874 > Screw: Steel zinc galvanised 5µm acc. to EN ISO 4042 cl. 5.8-Ø6 and cl.6.8-Ø7 Steel grey galvanised 10µm acc. to EN ISO 4042 cl. 5.8-Ø6 and cl.6.8-Ø7 Stainless steel AISI316 A4-70 acc. to ISO 3506-1
Durability	> Zinc galvanised or grey galvanised steel for dry internal conditions > Stainless Steel AISI316 A4-70 for other environmental conditions
Loading	Multiple use for non-structural applications (static or quasi-static load).
Fire Resistance	F90 for X5 Ø10 in the admissible load [Frk / (YM x YF)] is <= 0,8 kN
Fire Reaction	A1 acc. to EN 13501-1 for metal screw (for sleeve part see ETAG020 p.1 sect.5.2.1.)

4. Manufacturer (art. 11.5): **Friulsider SpA via trieste,1 - 33048 San Giovanni al Natisone (Udine) - Italy**

5. Authorised representative (art. 12.2): **Not Relevant**

6. System of Assessment AVCP (annex V): **System 2+**

7/8. Harmonised Specification & Notified Body:	Notified Body	System of Assessment	Reference	EN Norm or EAD Document
Technical Specification	ZAG nr.1404	2+	ETA-10/0425	ETAG020
Factory Product Control	ZAG nr.1404	2+	1404-CPD-1675	

9. Declared Performance: **See Annexes**

10. The performance of the product identified in points 1 and 2 is in conformity with declared performance in point 9. This declaration of performance is issued under the sole responsibility of Friulsider SpA. Signed for and behalf of the manufacturer by:

Name and functions	Place and date of issue	Signature
Sales Manager Fabrizio Fasan	San Giovanni al Natisone, 10-06-2015	

Annex I°

Declared performances according to <u>ETA-10/0425</u> - ETAG020 parts 1, 2, 3 and 4					
Design method ETAG020 Annex C					
ESSENTIAL CHARACTERISTICS			PERFORMANCE		
Installation parameters			FM-X5 Ø8	FM-X5 Ø10	
d_0	Nominal diameter of drill bit	[mm]	8	10	
h_{nom}	Minimum installation depth	[mm]	70	70	
h_{min}	Minimum thickness of the concrete member C12/15 - C16/20	[mm]	100	100	
s_{min}	Minimum spacing C12/15	[mm]	80	80	
c_{min}	Minimum edge distance C12/15	[mm]	80	80	
$C_{cr,N}$	Characteristic Edge distance C12/15	[mm]	140	140	
s_{min}	Minimum spacing C16/20	[mm]	60	60	
c_{min}	Minimum edge distance C16/20	[mm]	60	60	
$C_{cr,N}$	Characteristic Edge distance C16/20	[mm]	100	100	
h_{min}	Minimum thickness of the masonry member and AAC	[mm]	≥ 106 see under		
s_{min}	Minimum spacing in masonry and AAC - single anchor	[mm]	250	250	
c_{min}	Minimum edge distance in masonry and AAC - single anchor	[mm]	100	100	
s_{1min}	Spacing perpendicular to free edge in masonry and AAC - anchor group	[mm]	200	200	
s_{2min}	Spacing parallel to free edge in masonry and AAC - anchor group	[mm]	400	400	
c_{min}	Minimum edge distance in masonry and AAC - anchor group	[mm]	100	100	
Characteristic Bending resistance screw in Concrete, masonry and Autoclaved Aerated Concrete (AAC)					
$M_{Rk,s}$	Characteristic bending resistance <u>Galvanised Steel</u>	[Nm]	8,6	16,8	
	Characteristic bending resistance <u>Stainless Steel A4-70</u>	[Nm]	13,6	24,8	
$\gamma_{Ms}^{1)}$	Partial safety factor <u>Galvanised Steel</u>	[-]	1,25		
	Partial safety factor <u>Stainless Steel A4-70</u>	[-]	1,56		
Characteristic TENSION Resistance failure of screw for use in CONCRETE					
$N_{Rk,s}$	Tension Steel characteristic failure <u>Galvanised Steel</u>	[kN]	11,0	18,1	
	Tension Steel characteristic failure <u>Stainless Steel A4-70</u>	[kN]	16,5	25,0	
$\gamma_{ms,N}^{1)}$	Partial safety factor for tension steel failure <u>Galvanised Steel</u>	[-]	1,5		
	Partial safety factor for tension steel failure <u>Stainless Steel A4-70</u>	[-]	1,9		
Characteristic SHEAR Resistance failure of screw for use in CONCRETE					
$V_{Rk,s}$	Shear Steel characteristic failure <u>Galvanised Steel</u>	[kN]	5,5	9,0	
	Shear Steel characteristic failure <u>Stainless Steel A4-70</u>	[kN]	8,2	12,5	
$\gamma_{ms,V}^{1)}$	Partial safety factor for shear steel failure <u>Galvanised Steel</u>	[-]	1,25		
	Partial safety factor for shear steel failure <u>Stainless Steel A4-70</u>	[-]	1,56		
PULL-OUT failure in CONCRETE (plastic anchor)			FM-X5 Ø8	FM-X5 Ø10	
$N_{Rk,p}$	Tension characteristic load in cracked concrete C12/15	$24^{\circ}C^{2)} / 40^{\circ}C^{3)}$	[kN]	1,5	2,5
	Tension characteristic load in cracked concrete C12/15	$50^{\circ}C^{2)} / 80^{\circ}C^{3)}$	[kN]	0,75	1,5
	Tension characteristic load in cracked concrete C16/20	$24^{\circ}C^{2)} / 40^{\circ}C^{3)}$	[kN]	2,5	3,5
	Tension characteristic load in cracked concrete C16/20	$50^{\circ}C^{2)} / 80^{\circ}C^{3)}$	[kN]	1,2	2,5
$\gamma_{mc}^{1)}$	Partial safety factor	[-]	1,8		
Displacement under TENSION and SHEAR loading in CONCRETE					
N	Service tension load in concrete C16/20	[kN]	1,0	1,4	
δ_{N0}	Short term displacement under tension load	[mm]	3,8	1,7	
$\delta_{N\infty}$	Long term displacement under tension load	[mm]	7,5	3,6	
V	Service shear load in concrete	[kN]	1,0	1,4	
δ_{V0}	Short term displacement under shear load	[mm]	1,6	0,9	
$\delta_{V\infty}$	Long term displacement under tension load	[mm]	2,4	1,35	

¹⁾ In absence of other national regulations; ²⁾ Maximum long term temperature; ³⁾ Maximum short term temperature.

Annex II°

Declared performances according to <u>ETA-10/0425</u> - ETAG020 parts 1, 2, 3 and 4					
Design method ETAG020 Annex C					
ESSENTIAL CHARACTERISTICS			PERFORMANCE		
			FM-X5 Ø8	FM-X5 Ø10	
Characteristic Resistance for single anchor in Solid clay Brick $f_b \geq 43,8$ [MPa] $\rho \geq 1,8$ [kg/dm³] $h_{min} \geq 120$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	3,5	3,5
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	2,0	2,5
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Hammer drilling	
Characteristic Resistance for single anchor in Hollow clay Brick - Bimattone $f_b \geq 27,3$ [MPa] $\rho \geq 0,9$ [kg/dm³] $h_{min} \geq 120$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	1,5	1,5
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,9	1,2
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Hollow clay Brick - Alveolater Swiss heavy $f_b \geq 13,8$ [MPa] $\rho \geq 0,9$ [kg/dm³] $h_{min} \geq 250$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	1,5	1,5
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,6	1,2
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Hollow clay Brick - Alveolater Incastro 35 $f_b \geq 10,9$ [MPa] $\rho \geq 0,8$ [kg/dm³] $h_{min} \geq 350$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	1,5	1,5
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,75	1,2
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Hollow clay Brick - Blocco Leggero $f_b \geq 7$ [MPa] $\rho \geq 0,5$ [kg/dm³] $h_{min} \geq 120$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	0,9	0,9
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,4	0,6
γ_{Mm} ⁴⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Hollow clay Brick - Poroton $f_b \geq 22$ [MPa] $\rho \geq 0,9$ [kg/dm³] $h_{min} \geq 250$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	1,5	2,0
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,9	1,2
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Hollow clay Brick - Leopard BP category 1HD $f_b \geq 30$ [MPa] $\rho \geq 1,3$ [kg/dm³] $h_{min} \geq 106$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	2,0	1,5
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,9	0,9
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Hollow Brick light weight concrete BC 203 $f_b \geq 4$ [MPa] $\rho \geq 0,95$ [kg/dm³] $h_{min} \geq 200$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	0,75	0,6
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,3	0,6
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,5	
	Drill Method		[-]	Rotary drilling	
Characteristic Resistance for single anchor in Autoclaved Aerated Concrete (AAC) $f_b \geq 2,5$ [MPa] $\rho \geq 0,5$ [kg/dm³] $h_{min} \geq 200$ mm					
F_{Rk}	Characteristic Resistance	24°C ²⁾ / 40°C ³⁾	[kN]	0,6	0,6
	Characteristic Resistance	50°C ²⁾ / 80°C ³⁾	[kN]	0,6	0,5
γ_{Mm} ¹⁾	Partial safety factor		[-]	2,0	
	Drill Method		[-]	Hammer drilling	

¹⁾ In absence of other national regulations; ²⁾ Maximum long term temperature; ³⁾ Maximum short term temperature.

Reach Directive EC 1907/2006 declaration:

We inform you that Friulsider is classified in the EC 1907/2006 Reach Directive as a Downstream-user of substances.

The product supplied does not contain substances classified as SVHC according to the Candidate List in a concentration equal or greater than 0.1% (weight / weight). Article 31 is not applicable to the present product.